



FOIL-EN--005-A

Storage of Semperit Rubber Foil

The storage conditions are defined by standard **DIN 7716 (ISO 2230)**.

A summary of the most important storage conditions are mentioned below.

The storage of Semperit Rubber Foil can be influenced by temperature, humidity, ozone, daylight, oil, solvents, corrosive liquids as well as damp or radioactive materials.

- Semperit Rubber Foils have to be stored in cool, dry, dust free and moderately aired conditions. It is not recommended to store Semperit Rubber Foil in outdoor ambience.
- **The optimum storage** temperature is between -10°C and $+15^{\circ}\text{C}$. The maximum storage temperature should not exceed $+25^{\circ}\text{C}$.
- A relative **air humidity** above 65% as well as condensation of water should be avoided.
- The products should be protected against sunlight and intensive artificial light (negative influence of UV).
- Since **ozone** has negative influence on rubber it is not recommended to store rubber foils in rooms with machines producing ozone, like electrical engines.
- Stock management principles of "**first in, first out**" are recommended for all rubber products.

All specifications, numbers, calculations, test values, and data mentioned here – which are the basis for our customer consultation – are in accordance with the latest engineering standards. As the operating conditions have an influence on product application, this information can only be used as a rough guideline. It is the sole responsibility of the customer to check the application conditions of each individual case, and whether the specified quality criteria of our products are adequate for the intended purpose. Improper use, excessive loading, or exposure to impermissible media can impair the product's function. Our experts will be happy to answer any questions you might have. Text and pictures, etc. remain in the ownership of Semperit Technische Produkte Gesellschaft m.b.H. The pictures and graphics shown are only representative images. No liability is accepted for mistakes or printing errors and data is subject to change at any time. Copying and distribution in any form whatsoever, in whole or in part, only with the express written consent of Semperit. Copyright © Semperform. 2018. All rights reserved.

semperform® 
A MEMBER OF THE SEMPERIT-GROUP

Semperit Technische Produkte Gesellschaft m.b.H.
Triester Bundesstraße 26, 2632 Wimpassing, Austria
Telefon +43 2630 310-667
Telefax +43 2630 310 288
E-Mail: rubberfoils@semperitgroup.com
Internet: www.semperform.com